

New, High Reach Demolition Boom, to Fit Cat 349, A02929

ijscheckel.com/product/new-high-reach-demolition-boom-to-fit-cat-349-a02929/



Description

New Ultra High Reach Demolition Boom Set, to fit Cat 349. 96'6" Total reach, w/ extra counterweight attachment included. Manufactured with Strenx 700F brand extreme duty structural steel from SSAB. **Read the Details:**

85 Foot, 3-Piece, Ultra High Reach Demolition Boom information:

- 85', 3-piece, Boom
- Main Boom section has a unique, modular separating quick coupling design, for easy on and off for transport.
- Stick end downsized to a Cat 330 size, DB series linkage.
- In the manufacture of this boom, automated machine welded joints were performed where accessible. The quality of this package is second to none.

- Strenx Brand 700F extreme duty structural steel, and Q690D Grade Steel were spec'd for this boom construction. This is 100,076 PSI structural steel. This steel is 30-50% higher priced than the Q345B grade 70,000 PSI steel that is used in most of these Long and High Reach booms in the industry.
- High OEM Quality steel hydraulic plumping lines, with extra heavy clamps used throughout boom.
- Highest quality dimpled brass bushings used throughout the boom joints.
- Steel grease line plumbing to all joints.
- Boom weight 22,000 Pounds.
- Boom rated for 5,500 pound work tool.

Auxiliary Counterweight information:

- 12,000 pound auxiliary center section counterweight added to be added to machine.
- Carefully designed to maintain the existing body lines. Easy on / off if needed.
- Rear counterweight removes same as factory intended.
- We have a hydraulic tilt cab platform in stock as well for additional money, if interested in using that with this demo boom set.

3 ways to contact us - Call sales at **563-872-4112**. If you prefer to text, text Josh @ **563-590-9903**, or email **sales@jjscheckel.com**.

Ready to ship! It is located at our facility in Bellevue, Iowa.

Price: \$128,000